



## FS38C

Standard	EN ISO 20345:2011
Category	SIP SRC
Size Range	UK 3 - 13   EU 36 - 48
Colour	Black
Slip Resistance	SRC

**FS38C:** Non-metallic lace-up safety gibson ideal for industrial office use. Composite cap and midsole protection. Antistatic protection and heel energy absorption. Black leather lace-up shoe with three eyelets. Padded collar for ankle support and comfort. Conforms to EN ISO 20345:2011 Safety Footwear Standards. Dual Density PU outsole. Toe protection tested to 200 Joules impact. Midsole penetration resistant to 1100 newtons. Passes SRC slip resistance standards.

<b>Upper</b>	Cow Action Leather	<b>Construction</b>	Injection
<b>Inner Lining</b>	Breathable Mesh	<b>Outsole</b>	Dual Density PU/PU
<b>Footbed</b>	Removable EVA Footbed	<b>Weight</b>	600 grams (half pair size 8)
<b>Impact Resistance</b>	200 Joules Fibre Glass Composite Toe Cap	<b>Penetration Resistance</b>	Non-Metallic Anti-Penetration Midsole - Min. 1100N

### FEATURES

- ◆ Lightweight and Flexible Safety Boot
- ◆ Smooth Action Leather Upper
- ◆ Moisture Wicking Breathable Mesh Lining
- ◆ Padded PU Collar
- ◆ Padded PU Tongue
- ◆ Durable Dual Density PU Outsole
- ◆ Removable EVA Footbed
- ◆ Antistatic
- ◆ Energy Absorbent Heel
- ◆ Oil Resistant Outsole
- ◆ Metal Free

**Care Advice:** To enhance the life & performance of the footwear, upper should be kept clean & dry. Dry/damp cloth or shoe polish/spray to be used as per the need. Sole to be checked and clean regularly to maintain its traction. Any obvious damage in footwear may reduce full protection and must be replaced.